

COB

XF+ 0.7

Option ID 1018 · XF+ · 0.78 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	COB
Pixel pitch	0.7813 mm
Brightness	600 nit
Refresh rate	3840 Hz
Max frame rate	60 Hz
Colour processing	26 bit
Scan direction	vertical
Viewing angle H / V	160° / 160°

MECHANICAL

Cabinet (W x H x D)	600 x 337.5 x 42 mm
Module (W x H)	150 x 168.75 mm
Cabinet resolution	768 x 432 px
Cabinet area	0.2025 m²
Cabinet weight	5.2 kg
Cabinet material	Die-Cast
Power max / typ.	375 / 125 W/m²
Heat dissipation	1,280 BTU/h/m²
IP rating	IP54 / IP32
Condition	indoor

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-20°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100V~240V, 50~60 Hz
Typical lifetime	100000 h
Certifications	Pantone, Pantone Skintone
LED configuration	Common Cathode
Bond wire	Wireless