

SMD

XF+ 1.5

Option ID 388 · XF+ · 1.56 mm pitch



REAR / SIDE PICTURES:



XF+ SERIES: PANEL, ERMAC SYSTEM COMPONENTS AND CABINET DIMENSIONS

OPTICAL & PERFORMANCE

LED technology	SMD
Pixel pitch	1.5625 mm
LED package	Standard
Brightness	800 nit
Refresh rate	3840 Hz
Max frame rate	120 Hz
Colour processing	26 bit
Scan direction	Horizontal
Viewing angle H / V	150° / 130°

MECHANICAL

Cabinet (W x H x D)	300 x 337.5 x 38 mm
Module (W x H)	300 x 168.75 mm
Cabinet resolution	192 x 216 px
Cabinet area	0.1013 m²
Cabinet weight	3.5 kg
Cabinet material	Die-Cast
Power max / typ.	650 / 350 W/m²
Heat dissipation	2,218 BTU/h/m²
IP rating	IP30
Condition	indoor

ELECTRICAL, ENVIRONMENTAL & COMPLIANCE

Working temperature	-10°C~+60°C
Storage temperature	-10°C~+40°C
Working humidity	10~85%RH
AC input	100~240, 50~60 Hz
Typical lifetime	100000 h
Certifications	Pantone Pantone Skintone DICOM
LED configuration	Common Anode
Bond wire	Copper